

FORKLIFT JACKS & STANDS

TOTALSOURCE®

FEATURED PRODUCTS

SY15000



- Meets CE requirements

Specifications	U.S. Units	Metric Units
Capacity	15,442lbs	7 mt
Power	Two-Speed Hydraulic Pump	
Min. starting height	2¼"	57mm
Max. lifting height	16"	406mm
Forward reach	7"	178mm
Width	9"	228mm
Shipping weight	92lbs	42kg


SY8000



- Meets CE requirements
- 2 year limited warranty
- Replacement parts for old style Gray® (FLJ model jacks) also available
- Made in the U.S.A.

Specifications	U.S. Units	Metric Units
Capacity	8,000lbs	3.6mt
Start pad height (notch)	2.25"	57mm
Start pad height (serrated pad)	2.5"	63mm
Raised height (maximum)	16"	406mm
Width	8"	203mm
Weight	68lbs	30.6kg
Reach (raised position)	7"	117mm
(Distance from hydraulic cylinder to lift pad)		

SY400



- 4 position height adjustment
- Made in the U.S.A.
- Sold in pairs

Specifications	U.S. Units	Metric Units
Capacity	30,870lbs	13.9mt (pair)
Pad dimensions	2.5" x 3.5"	63mm x 89mm
Start pad height	9.5"	241mm
Raised height	16"	406mm
Height increments	2"	50mm
Weight (pair)	31lbs	14kg
Base	8"sq	203mm