

CLASS II SIDE-SHIFTERS AND LOAD BACKRESTS

TOTALSOURCE®

FEATURED PRODUCTS



These Side-Shifters are made using quality components and are easy to mount and maintain. The double effect cylinder allows for speed when shifting in both directions.

Side-Shifter Features:

- # 6 JIC Fittings
- Place loads quickly without repositioning the truck
- Hydraulic cylinder can be easily disassembled for complete maintenance
- Replacement parts available
- 2 year warranty

Load Back Rest Features

- Rack-like extension
- Helps stop load from shifting backward

Class II	Capacity / Width	Bolts Per Side	Frame	Min. Truck Carriage Width	Overall Height	Lost Load	HCG	VCG	Weight	Stroke
SYTRF225.082-02	5500lb 0820 mm	2	32.283" 820 mm	27.56" 700 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.082-04	5500lb 0820 mm	4	32.283" 820 mm	27.56" 700 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.092-02	5500lb 0920 mm	2	36.22" 920 mm	31.5" 800 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.092-04	5500lb 0920 mm	4	36.22" 920 mm	31.5" 800 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.093-02	5500lb 0930 mm	2	36.61" 930 mm	31.5" 800 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.093-04	5500lb 0930 mm	4	36.61" 930 mm	31.5" 800 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.094-02	5500lb 0940 mm	2	37.01" 940 mm	31.5" 800 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.094-04	5500lb 0940 mm	4	37.01" 940 mm	31.5" 800 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.098-02	5500lb 0980 mm	2	38.58" 980 mm	33.5" 850 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.098-04	5500lb 0980 mm	4	38.58" 980 mm	33.5" 850 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.100-02	5500lb 1000 mm	2	39.37" 1000 mm	33.5" 850 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.100-04	5500lb 1000 mm	4	39.37" 1000 mm	33.5" 850 mm	18.189" 462 mm	2.76" 70 mm	34	260	103lbs 47kg	100+100 mm
SYTRF225.104-02	5500lb 1040 mm	2	40.95" 1040 mm	33.5" 850 mm	18.189" 462 mm	2.76" 70 mm	34	260	112lbs 51kg	100+100 mm
SYTRF225.104-04	5500lb 1040 mm	4	40.95" 1040 mm	33.5" 850 mm	18.189" 462 mm	2.76" 70 mm	34	260	112lbs 51kg	100+100 mm
SYTRF225.107-02	5500lb 1070 mm	2	42.13" 1070 mm	33.5" 850 mm	18.189" 462 mm	2.76" 70 mm	34	260	112lbs 51kg	100+100 mm
SYTRF225.107-04	5500lb 1070 mm	4	42.13" 1070 mm	33.5" 850 mm	18.189" 462 mm	2.76" 70 mm	34	260	112lbs 51kg	100+100 mm
SYTRF225.110-02	5500lb 1100 mm	2	43.31" 1100 mm	35.43" 900 mm	18.189" 462 mm	2.76" 70 mm	34	260	112lbs 51kg	100+100 mm
SYTRF225.110-04	5500lb 1100 mm	4	43.31" 1100 mm	35.43" 900 mm	18.189" 462 mm	2.76" 70 mm	34	260	112lbs 51kg	100+100 mm
SYTRF225.115-02	5500lb 1150 mm	2	45.28" 1150 mm	35.43" 900 mm	18.189" 462 mm	2.76" 70 mm	34	260	112lbs 51kg	100+100 mm
SYTRF225.115-04	5500lb 1150 mm	4	45.28" 1150 mm	35.43" 900 mm	18.189" 462 mm	2.76" 70 mm	34	260	112lbs 51kg	100+100 mm
SYTRF225.122-02	5500lb 1220 mm	2	48.03" 1220 mm	37.4" 950 mm	18.189" 462 mm	2.76" 70 mm	34	260	114lbs 52kg	100+100 mm
SYTRF225.122-04	5500lb 1220 mm	4	48.03" 1220 mm	37.4" 950 mm	18.189" 462 mm	2.76" 70 mm	34	260	114lbs 52kg	100+100 mm
SYTRF225.140-02	5500lb 1400 mm	2	55.12" 1400 mm	43.31" 1100 mm	18.189" 462 mm	2.76" 70 mm	34	260	114lbs 52kg	100+100 mm
SYTRF225.140-04	5500lb 1400 mm	4	55.12" 1400 mm	43.31" 1100 mm	18.189" 462 mm	2.76" 70 mm	34	260	114lbs 52kg	100+100 mm

Class II	Description
SYLBR225.082-02	LOAD BACK REST 32.28 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.082-04	LOAD BACK REST 32.28 IN X 48 IN - 4 BOLTS PER SIDE CLASS II
SYLBR225.092-02	LOAD BACK REST 36.22 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.092-04	LOAD BACK REST 36.22 IN X 48 IN - 4 BOLTS PER SIDE CLASS II
SYLBR225.093-02	LOAD BACK REST 36.61 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.093-04	LOAD BACK REST 36.61 IN X 48 IN - 4 BOLTS PER SIDE CLASS II
SYLBR225.094-02	LOAD BACK REST 37.00 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.094-04	LOAD BACK REST 37.00 IN X 48 IN - 4 BOLTS PER SIDE CLASS II
SYLBR225.098-02	LOAD BACK REST 38.58 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.098-04	LOAD BACK REST 38.58 IN X 48 IN - 4 BOLTS PER SIDE CLASS II
SYLBR225.100-02	LOAD BACK REST 39.37 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.100-04	LOAD BACK REST 39.37 IN X 48 IN - 4 BOLTS PER SIDE CLASS II

Class II	Description
SYLBR225.104-02	LOAD BACK REST 40.94 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.104-04	LOAD BACK REST 40.94 IN X 48 IN - 4 BOLTS PER SIDE CLASS II
SYLBR225.107-02	LOAD BACK REST 42.12 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.107-04	LOAD BACK REST 42.12 IN X 48 IN - 4 BOLTS PER SIDE CLASS II
SYLBR225.110-02	LOAD BACK REST 43.30 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.110-04	LOAD BACK REST 43.30 IN X 48 IN - 4 BOLTS PER SIDE CLASS II
SYLBR225.115-02	LOAD BACK REST 45.27 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.115-04	LOAD BACK REST 45.27 IN X 48 IN - 4 BOLTS PER SIDE CLASS II
SYLBR225.122-02	LOAD BACK REST 48.03 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.122-04	LOAD BACK REST 48.03 IN X 48 IN - 4 BOLTS PER SIDE CLASS II
SYLBR225.140-02	LOAD BACK REST 55.11 IN X 48 IN - 2 BOLTS PER SIDE CLASS II
SYLBR225.140-04	LOAD BACK REST 55.11 IN X 48 IN - 4 BOLTS PER SIDE CLASS II

CLASS III SIDE-SHIFTERS AND LOAD BACKRESTS

TOTALSOURCE®

FEATURED PRODUCTS



These Side-Shifters are made using quality components and are easy to mount and maintain. The double effect cylinder allows for speed when shifting in both directions.

Side-Shifter Features:

- # 6 JIC Fittings
- Place loads quickly without repositioning the truck
- Hydraulic cylinder can be easily disassembled for complete maintenance
- Replacement parts available
- 2 year warranty

Load Back Rest Features

- Rack-like extension
- Helps stop load from shifting backward

Class III	Capacity / Width	Bolts Per Side	Frame	Min. Truck Carriage Width	Overall Height	Lost Load	HCG	VCG	Weight	Stroke
SYTRF335.096-02	7500lb 0960 mm	2	37.8" 960 mm	33.5" 850 mm	22.56" 573 mm	3.15" 80 mm	45	300	108lbs 49kg	100+100 mm
SYTRF335.096-04	7500lb 0960 mm	4	37.8" 960 mm	33.5" 850 mm	22.56" 573 mm	3.15" 80 mm	45	300	108lbs 49kg	100+100 mm
SYTRF335.100-02	7500lb 1000 mm	2	39.37" 1000 mm	35.43" 900 mm	22.56" 573 mm	3.15" 80 mm	45	300	108lbs 49kg	100+100 mm
SYTRF335.100-04	7500lb 1000 mm	4	39.37" 1000 mm	35.43" 900 mm	22.56" 573 mm	3.15" 80 mm	45	300	108lbs 49kg	100+100 mm
SYTRF350.100-02	11000lb 1000 mm	2	39.37" 1000 mm	35.43" 900 mm	22.56" 573 mm	3.15" 80 mm	39	300	253lbs 115kg	100+100 mm
SYTRF350.100-04	11000lb 1000 mm	4	39.37" 1000 mm	35.43" 900 mm	22.56" 573 mm	3.15" 80 mm	39	300	253lbs 115kg	100+100 mm
SYTRF335.102-02	7500lb 1020 mm	2	40.16" 1020 mm	35.43" 900 mm	22.56" 573 mm	3.15" 80 mm	45	300	108lbs 49kg	100+100 mm
SYTRF335.102-04	7500lb 1020 mm	4	40.16" 1020 mm	35.43" 900 mm	22.56" 573 mm	3.15" 80 mm	45	300	108lbs 49kg	100+100 mm
SYTRF350.102-02	11000lb 1020 mm	2	40.16" 1020 mm	35.43" 900 mm	22.56" 573 mm	3.15" 80 mm	39	300	253lbs 115kg	100+100 mm
SYTRF350.102-04	11000lb 1020 mm	4	40.16" 1020 mm	35.43" 900 mm	22.56" 573 mm	3.15" 80 mm	39	300	253lbs 115kg	100+100 mm
SYTRF350.115-04	11000lb 1150 mm	4	45.28" 1150 mm	37.4" 950 mm	22.56" 573 mm	3.15" 80 mm	39	300	275lbs 125kg	100+100 mm
SYTRF350.115-02	11000lb 1150 mm	2	45.28" 1150 mm	37.4" 950 mm	22.56" 573 mm	3.15" 80 mm	39	300	275lbs 125kg	100+100 mm
SYTRF335.115-02	7500lb 1150 mm	2	45.28" 1150 mm	39.37" 1000 mm	22.56" 573 mm	3.15" 80 mm	45	300	176lbs 80kg	100+100 mm
SYTRF335.115-04	7500lb 1150 mm	4	45.28" 1150 mm	39.37" 1000 mm	22.56" 573 mm	3.15" 80 mm	45	300	176lbs 80kg	100+100 mm
SYTRF335.120-02	7500lb 1200 mm	2	47.24" 1200 mm	39.37" 1000 mm	22.56" 573 mm	3.15" 80 mm	45	300	231lbs 105kg	100+100 mm
SYTRF335.120-04	7500lb 1200 mm	4	47.24" 1200 mm	39.37" 1000 mm	22.56" 573 mm	3.15" 80 mm	45	300	231lbs 105kg	100+100 mm
SYTRF350.120-02	11000lb 1200 mm	2	47.24" 1200 mm	39.37" 1000 mm	22.56" 573 mm	3.15" 80 mm	39	300	286lbs 130kg	100+100 mm
SYTRF350.120-04	11000lb 1200 mm	4	47.24" 1200 mm	39.37" 1000 mm	22.56" 573 mm	3.15" 80 mm	39	300	286lbs 130kg	100+100 mm
SYTRF350.130-02	11000lb 1300 mm	2	51.181 1300 mm	43.31" 1100 mm	22.56" 573 mm	3.15" 80 mm	39	300	286lbs 130kg	100+100 mm
SYTRF350.130-04	11000lb 1300 mm	4	51.181 1300 mm	43.31" 1100 mm	22.56" 573 mm	3.15" 80 mm	39	300	286lbs 130kg	100+100 mm
SYTRF350.150-02	11000lb 1500 mm	2	59.06" 1500 mm	47.24" 1200 mm	22.56" 573 mm	3.15" 80 mm	40	300	341lbs 155kg	100+100 mm
SYTRF350.150-04	11000lb 1500 mm	4	59.06" 1500 mm	47.24" 1200 mm	22.56" 573 mm	3.15" 80 mm	40	300	341lbs 155kg	100+100 mm
SYTRF335.150-02	7500lb 1500 mm	2	59.06" 1500 mm	47.24" 1200 mm	22.56" 573 mm	3.15" 80 mm	45	300	242lbs 110kg	100+100 mm
SYTRF335.150-04	7500lb 1500 mm	4	59.06" 1500 mm	47.24" 1200 mm	22.56" 573 mm	3.15" 80 mm	45	300	242lbs 110kg	100+100 mm

Class III	Description
SYLBR335.096-02	LOAD BACK REST 37.79 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR335.096-04	LOAD BACK REST 37.79 IN X 48 IN - 4 BOLTS PER SIDE CLASS III
SYLBR335.100-02	LOAD BACK REST 39.37 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR335.100-04	LOAD BACK REST 39.37 IN X 48 IN - 4 BOLTS PER SIDE CLASS III
SYLBR335.102-02	LOAD BACK REST 40.15 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR335.102-04	LOAD BACK REST 40.15 IN X 48 IN - 4 BOLTS PER SIDE CLASS III
SYLBR335.115-02	LOAD BACK REST 45.27 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR335.115-04	LOAD BACK REST 45.27 IN X 48 IN - 4 BOLTS PER SIDE CLASS III
SYLBR335.120-02	LOAD BACK REST 47.24 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR335.120-04	LOAD BACK REST 47.24 IN X 48 IN - 4 BOLTS PER SIDE CLASS III
SYLBR335.150-02	LOAD BACK REST 59.05 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR335.150-04	LOAD BACK REST 59.05 IN X 48 IN - 4 BOLTS PER SIDE CLASS III

Class III	Description
SYLBR350.100-02	LOAD BACK REST 39.37 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR350.100-04	LOAD BACK REST 39.37 IN X 48 IN - 4 BOLTS PER SIDE CLASS III
SYLBR350.102-02	LOAD BACK REST 40.15 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR350.102-04	LOAD BACK REST 40.15 IN X 48 IN - 4 BOLTS PER SIDE CLASS III
SYLBR350.115-02	LOAD BACK REST 45.27 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR350.115-04	LOAD BACK REST 45.27 IN X 48 IN - 4 BOLTS PER SIDE CLASS III
SYLBR350.120-02	LOAD BACK REST 47.24 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR350.120-04	LOAD BACK REST 47.24 IN X 48 IN - 4 BOLTS PER SIDE CLASS III
SYLBR350.130-02	LOAD BACK REST 51.18 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR350.130-04	LOAD BACK REST 51.18 IN X 48 IN - 4 BOLTS PER SIDE CLASS III
SYLBR350.150-02	LOAD BACK REST 59.05 IN X 48 IN - 2 BOLTS PER SIDE CLASS III
SYLBR350.150-04	LOAD BACK REST 59.05 IN X 48 IN - 4 BOLTS PER SIDE CLASS III

CLASS IV SIDE-SHIFTERS AND LOAD BACKRESTS

TOTALSOURCE®

FEATURED PRODUCTS



These Side-Shifters are made using quality components and are easy to mount and maintain. The double effect cylinder allows for speed when shifting in both directions.

Side-Shifter Features:

- # 6 JIC Fittings
- Place loads quickly without repositioning the truck
- Hydraulic cylinder can be easily disassembled for complete maintenance
- Replacement parts available
- 2 year warranty

Load Back Rest Features

- Rack-like extension
- Helps stop load from shifting backward

Class IV	Capacity / Width	Bolts Per Side	Frame	Min. Truck Carriage Width	Overall Height	Lost Load	HCG	VCG	Weight	Stroke
SYTRF460.119-02	13000lb 1190 mm	2	46.85" 1190 mm	41.34" 1050 mm	27.76" 705 mm	3.94" 100 mm	50	350	440lbs 200kg	150+150 mm
SYTRF460.119-04	13000lb 1190 mm	4	46.85" 1190 mm	41.34" 1050 mm	27.76" 705 mm	3.94" 100 mm	50	350	440lbs 200kg	150+150 mm
SYTRF460.150-02	13000lb 1500 mm	2	59.06" 1500 mm	47.24" 1200 mm	27.76" 705 mm	3.94" 100 mm	50	350	616lbs 280kg	150+150 mm
SYTRF460.150-04	13000lb 1500 mm	4	59.06" 1500 mm	47.24" 1200 mm	27.76" 705 mm	3.94" 100 mm	50	350	616lbs 280kg	150+150 mm
SYTRF480.150-02	17000lb 1500 mm	2	59.06" 1500 mm	47.24" 1200 mm	27.76" 705 mm	3.94" 100 mm	55	350	660lbs 300kg	150+150 mm
SYTRF480.150-04	17000lb 1500 mm	4	59.06" 1500 mm	47.24" 1200 mm	27.76" 705 mm	3.94" 100 mm	55	350	660lbs 300kg	150+150 mm
SYTRF460.180-04	13000lb 1800 mm	4	70.87" 1800 mm	57.1" 1450 mm	27.76" 705 mm	3.94" 100 mm	50	350	616lbs 280kg	150+150 mm
SYTRF480.180-02	17000lb 1800 mm	2	70.87" 1800 mm	57.1" 1450 mm	27.76" 705 mm	3.94" 100 mm	55	350	693lbs 315kg	150+150 mm
SYTRF480.180-04	17000lb 1800 mm	4	70.87" 1800 mm	57.1" 1450 mm	27.76" 705 mm	3.94" 100 mm	55	350	693lbs 315kg	150+150 mm
SYTRF460.180-02	13000lb 1800 mm	2	70.87" 1800 mm	57.1" 1450 mm	27.76" 705 mm	3.94" 100 mm	50	350	616lbs 280kg	150+150 mm
SYTRF480.200-02	17000lb 2000 mm	2	78.74" 2000 mm	64.96" 1650 mm	27.76" 705 mm	3.94" 100 mm	55	350	737lbs 335kg	150+150 mm
SYTRF480.200-04	17000lb 2000 mm	4	78.74" 2000 mm	64.96" 1650 mm	27.76" 705 mm	3.94" 100 mm	55	350	737lbs 335kg	150+150 mm
SYTRF460.119-02	13000lb 1190 mm	2	46.85" 1190 mm	41.34" 1050 mm	27.76" 705 mm	3.94" 100 mm	50	350	440lbs 200kg	150+150 mm
SYTRF460.119-04	13000lb 1190 mm	4	46.85" 1190 mm	41.34" 1050 mm	27.76" 705 mm	3.94" 100 mm	50	350	440lbs 200kg	150+150 mm
SYTRF460.150-02	13000lb 1500 mm	2	59.06" 1500 mm	47.24" 1200 mm	27.76" 705 mm	3.94" 100 mm	50	350	616lbs 280kg	150+150 mm
SYTRF460.150-04	13000lb 1500 mm	4	59.06" 1500 mm	47.24" 1200 mm	27.76" 705 mm	3.94" 100 mm	50	350	616lbs 280kg	150+150 mm
SYTRF480.150-02	17000lb 1500 mm	2	59.06" 1500 mm	47.24" 1200 mm	27.76" 705 mm	3.94" 100 mm	55	350	660lbs 300kg	150+150 mm
SYTRF480.150-04	17000lb 1500 mm	4	59.06" 1500 mm	47.24" 1200 mm	27.76" 705 mm	3.94" 100 mm	55	350	660lbs 300kg	150+150 mm
SYTRF460.180-04	13000lb 1800 mm	4	70.87" 1800 mm	57.1" 1450 mm	27.76" 705 mm	3.94" 100 mm	50	350	616lbs 280kg	150+150 mm
SYTRF480.180-02	17000lb 1800 mm	2	70.87" 1800 mm	57.1" 1450 mm	27.76" 705 mm	3.94" 100 mm	55	350	693lbs 315kg	150+150 mm
SYTRF480.180-04	17000lb 1800 mm	4	70.87" 1800 mm	57.1" 1450 mm	27.76" 705 mm	3.94" 100 mm	55	350	693lbs 315kg	150+150 mm
SYTRF460.180-02	13000lb 1800 mm	2	70.87" 1800 mm	57.1" 1450 mm	27.76" 705 mm	3.94" 100 mm	50	350	616lbs 280kg	150+150 mm
SYTRF480.200-02	17000lb 2000 mm	2	78.74" 2000 mm	64.96" 1650 mm	27.76" 705 mm	3.94" 100 mm	55	350	737lbs 335kg	150+150 mm
SYTRF480.200-04	17000lb 2000 mm	4	78.74" 2000 mm	64.96" 1650 mm	27.76" 705 mm	3.94" 100 mm	55	350	737lbs 335kg	150+150 mm

Class IV	Description
SYLBR460.119-02	LOAD BACK REST 46.85 IN X 48 IN - 2 BOLTS PER SIDE CLASS IV
SYLBR460.119-04	LOAD BACK REST 46.85 IN X 48 IN - 4 BOLTS PER SIDE CLASS IV
SYLBR460.150-02	LOAD BACK REST 59.05 IN X 48 IN - 2 BOLTS PER SIDE CLASS IV
SYLBR460.150-04	LOAD BACK REST 59.05 IN X 48 IN - 4 BOLTS PER SIDE CLASS IV
SYLBR460.180-02	LOAD BACK REST 70.86 IN X 48 IN - 2 BOLTS PER SIDE CLASS IV
SYLBR460.180-04	LOAD BACK REST 70.86 IN X 48 IN - 4 BOLTS PER SIDE CLASS IV

Class IV	Description
SYLBR480.150-02	LOAD BACK REST 59.05 IN X 48 IN - 2 BOLTS PER SIDE CLASS IV
SYLBR480.150-04	LOAD BACK REST 59.05 IN X 48 IN - 4 BOLTS PER SIDE CLASS IV
SYLBR480.180-02	LOAD BACK REST 70.86 IN X 48 IN - 2 BOLTS PER SIDE CLASS IV
SYLBR480.180-04	LOAD BACK REST 70.86 IN X 48 IN - 4 BOLTS PER SIDE CLASS IV
SYLBR480.200-02	LOAD BACK REST 78.74 IN X 48 IN - 2 BOLTS PER SIDE CLASS IV
SYLBR480.200-04	LOAD BACK REST 78.74 IN X 48 IN - 4 BOLTS PER SIDE CLASS IV